

# **CLECO NEOTEK ELECTRIC NUTRUNNER**

The Cleco NeoTek series consists of electric nutrunners equipped with torque sensors, designed for the varying needs of precision and speed in assembly work. The nutrunners are available in various models covering a wide range of torque levels and are built to last, capable of performing over one million tightening cycles without requiring maintenance.

The NeoTek series features a thinner and more flexible cable than competitors, ensuring ease of use and ergonomics. The nutrunners are equipped with clear and audible signals and four programmable LED indicator rings on the handle. The extensive range includes pistol, inline, angle, and specialized models with torque sensors up to 850 Nm, while older models can achieve up to 2,000 Nm



in



# **CLECO CONTROLLERS**

The mPro control units, which receive real-time data from Cleco nutrunners, are a reliable choice for maximizing the potential of nutrunners in assembly environments. Real-time recording of tightening tasks and comprehensive connectivity and communication capabilities ensure efficient tool usage in changing and challenging assembly line conditions. The extensive selection of control units provides a suitable match for every Cleco cordless and electric assembly nutrunner.

#### **MPR0400**

A user-friendly, versatile series of control units equipped with a precise touchscreen, the mPro400 is the crown jewel of Cleco's assembly tools. The range includes four different models, ensuring the right system for both individual wired nutrunners and up to sixteen wireless nutrunners. In addition to the latest Cleco wrench series, mPro400 is also compatible with the company's older torque nutrunners.





mPro400GCD-P/M mPro400GCD-SH

#### **MPR0300**

A simple yet versatile control unit designed for assembly lines that use individual torque nutrunners. The lightweight and compact mPro300, like its larger counterpart, features a precise touchscreen, making programming nutrunners and recording tightening tasks easier during operation.





mPro300

mPro250

#### **MPRO250**

Designed for use with Cleco's wireless assembly nutrunners, the mPro250 is the perfect choice for situations requiring a single control unit to manage multiple battery-powered Cleco nutrunners simultaneously. Its compact size and lightweight design make it easy to position the mPro250 in an optimal location at the worksite.

## **CHOOSING THE RIGHT CONTROL UNIT**

Controller	CellTek	CellCore	CellClutch	NeoTek	Intelligent spindles	Conventional spindles	Mini spindles	LiveWire	18/48	I-Wrench
mPro400GCD-P	~	V	~	V				· /	~	~
mPro400GCD-M	V	V	V					V		V
mPro400GCD-SH				V					V	
mPro400GCD-BTS					<b>V</b>					
mPro300GCD				V		<b>~</b>	V			
mPro300GCD-ST0						<b>V</b>				
mPro250	~	~	<b>V</b>					~		V
mPro250-AP	V	V	V					V		V
mPro250-AP-BT	V	~	~					~		V

Item	Nutrunners (wired + wireless)	Weight kg	Width mm	Height mm	Depth mm
mPro400GCD-P	1 + 15	13,7	266,7	381	288
mPro400GCD-M	0 + 16	9,7	266,7	381	288
mPro400GCD-SH	1 + 0	12,8	266,7	381	288
mPro400GCD-BTS	1 / 2 + 0	13,7	226,7	381	288
mPro300GCD	1 + 0	11,6	142	410	297
mPro300GCD-ST0	1 + 0	11,6	142	410	297
mPro250	0 + 16	8,2	144,5	406,5	333,4
mPro250-AP	0 + 12	8,2	144,5	406,5	333,4
mPro250-AP-BT	0 + 7	8,2	144,5	406,5	333,4



# **CLECO NEOTEK**

## **PISTOL NUTRUNNERS**

- Accurate torque transducer
- I Lightweight, smooth body and cable design
- 1 million cycles maintenance-free
- Repeatability & Accuracy with 2.0 Cm/Cmk at +/- 7%
- Configurable LED light rings
- Tactile & Audible Operator Feedback
- I Programmable Multi-function Buttons

Item	Torque range Nm	Free speed rpm	Weight kg	Lenght mm	Side to center mm	Drive
30-series						
30EPN05BD2	0,9 - 4,7	4 275	0,93	197	16,3	1/4" SQ
30EPN05BDQ	0,9 - 4,7	4 275	0,91	210	16,3	1/4" QC
30EPN12EAQ	3,9 - 11,6	1 650	1,00	229	16,3	1/4" QC
30EPN12FA3	3,9 - 11,6	1 650	0,98	214	16,3	3/8" SQ
30EPN19FB3	3,9 - 19,0	1 000	1,00	214	16,3	3/8" SQ
30EPN26FB3	5,1 - 26,0	750	1,00	214	16,3	3/8" SQ
50-series						
50EPN28FD3	5,6 - 28	2 125	1,58	256	16,3	3/8" SQ
50EPN43GD3	9,0 - 43	1 375	1,65	260	18,9	3/8" SQ
50EPN65HD4	14 - 66	900	2,14	288	22,0	1/2" SQ
50EPN85JD4	17 - 84	670	2,22	302	22,0	1/2" SQ
50EPN125KD4	25 - 123	455	2,62	313	28,0	1/2" SQ





## **SCRATCH COVER**

Item	Compatability
T50-1102812	30EPN05BDQ
T50-1102813	30EPN12EAQ, 30EPN19FB3, 30EPN26FB3



